

datasheet

Reception Seating Models 710, 712 & 713

#### Common Dimensions:

Overall Depth 30"
Overall Height 34.25"
Seat Depth 20.75"
Seat Height 18.5"
Arm Height 26.75"

# Lounge Single Seat Model 710:

Overall Width 28.5"
Inside Seat Width 22.25"
Product Weight 68 lbs
Shipping Cube 24.80 ft³

# Love Seat Two Seat Model 712:

Overall Width 55" Inside Seat Width 47.75" Product Weight 106 lbs Shipping Cube 43 ft<sup>3</sup>

#### Sofa Three Seat Model 713:

Overall Width 72.75"
Inside Seat Width 65.75"
Product Weight 125 lbs
Shipping Cube 53.2 ft<sup>3</sup>

Contact sales representative for more information.

### Features:

- Lounge, Love Seat and Sofa Models
- 4" raised legs allow for easy cleaning
- Metal legs available in Silver only
- Optional wood legs available in 18 OCI finishes
- Wood Tablet Option available in solid wood only with side stow
- Power Unit Option (2 USB, 1 Plug)

### **Product Warranty:**

- 10 year warranty on frame, 3 years on Fabric, Suspension and Foam
- Warranty applies only to single shift, standard commercial usage (8 hours/ day, 5 days/week)

# Metal Leg Finish:

Standard Brushed Silver



S - Silver

# **Optional Fabrics:**

Available in a range of graded fabrics and vinyls from grades 1 - 8. Choose from Momentum, Mayer, CF Stinson and more available upon request. Also available in Leather.

### Fabric Requirements:

Lounge:

COM: 4 yds. COL: 80 ft<sup>2</sup>

Love Seat:

COM: 5.5 yds. COL: 110 ft<sup>2</sup>

Sofa:

COM: 7 yds. COL: 140 ft<sup>2</sup>



### Construction:

### Seat:

- Plywood Seat frame: .75" thick, 7 ply
- Steel inserts provide metal-to-metal connections to other components
- Steel Spring suspension system

### Back:

- Plywood Back frame: .75" thick, 7 ply
- Steel inserts provide metal-to-metal connections to other components
- Steel Spring Back suspension system

### Arms:

- Plywood Arm frame: .75" thick, 7 ply
- Non-Woven suspension system behind foam cushion
- Fastened to base using metal-tometal connections

#### Base:

- Welded 14 gauge 1.5" square steel tubular base frame
- Frame fastened using metal-to-metal connections
- Black ABS non-marking glides

### Upholstery:

#### Seat:

- Can be upholstered in fabric, vinyl or leather
- Cushions are fixed to prevent removal (for public spaces)
- Seat bottom is sealed with liner

#### Arms and Back:

 Can be upholstered in fabric, vinyl, or leather

# Foam:

#### Seat:

• 4.5" thick HR foam

#### Back:

- 3" thick back foam
- Density: 1.8

#### Arms:

- Arm foam is .25" thick on top and sides of arms.
- Arm foam is .25" thick on front and back of arms.
- Density: 1.5 lbs

## **Product Durability:**

- Designed for an active weight capacity of 300 lbs per seat
- Meets and exceeds all applicable testing standards for safety and durability
- Manufactured in the U.S.A. under stringent quality standards

# Fire Rating:

 All fabric and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117) standards

#### Environmental:

- All foam is produced without using any ozone depleting chloroflouro chemicals.
- All wood used is TSCA compliant to help reduce and or eliminate formaldehyde emissions.

## Shipping:

The Tux Lite Line is delivered pre assembled by the OCI team of assemblers, bagged and wrapped for protection. Ships in a carton or blanket wrapped where available.

Please visit OCISeating.com for additional product information.

